Ontario Geological Survey
Aggregate Resources Inventory Paper 15

AGGREGATE RESOURCES INVENTORY OF SMITH TOWNSHIP PETERBOROUGH COUNTY SOUTHERN ONTARIO

by

Staff of the Engineering and Terrain Geology Section

Ontario Geological Survey

1980

Ontario
Ministry of
Natural
Resources

© OMNR-OGS 1980

Publications of the Ontario Ministry of Natural Resources, Geological Branch
and price list
are obtainable through the
Ontario Ministry of Natural Resources, Map Unit, Public Service Centre
Queen's Park, Toronto, Ontario
and
The Ontario Government Bookstore
880 Bay Street, Toronto, Ontario

Orders for publications should be accompanied by cheque
or money order, payable to the Treasurer of Ontario

ISSN 0708-2061
ISBN 0-7743-4878-X

This report was prepared by: Staff of the Engineering and Terrain Geology Section of the Ontario Geological Survey, Ontario Ministry of Natural Resources, 77 Grenville St., Toronto, M5S 1B3, Telephone (416) 965-1182.

Project Supervisor: Dale W. Scott
Text Prepared by: J. Z. Fraser
Compilation and Drafting by: Staff of the Aggregate Assessment Office

Parts of this publication may be quoted if credit is given to the Ontario Ministry of Natural Resources, Ontario Geological Survey. It is recommended that reference to this report be made in the following form:

Ontario Geological Survey
1980: Aggregate Resources Inventory of Smith Township, Peterborough County; Ontario Geological Survey, Aggregate Resources Inventory Paper 15, 33p., 6 tables, 3 maps, scale 1:50 000.

Every possible effort is made to insure the accuracy of the information contained in this report but the Ministry of Natural Resources does not assume any liability for errors that may occur. Source references are included in the report and users may wish to verify critical information.

CONTENTS

Page

Abstract v
Introduction 1
Part I - Inventory Methods 2
Field and Office Methods 2
Resource Tonnage Calculation Techniques 2
Sand and Gravel Resources 2
Bedrock Resources 3
Units and Definitions 3
Part II - Data Presentation and Interpretation 4
Map 1 Distribution of Sand and Gravel Deposits 4
Map 2 Selected Sand and Gravel Resource Areas 4
Site Specific Criteria 5
Deposit Size 5
Aggregate Quality 5
Location and Setting 6
Regional Considerations 6
Map 3 Bedrock Resources 7
Selection Criteria 7
Selected Resource Areas 7
Part III - Assessment of Aggregate Resources in Smith Township 9
Location and Population 9
Physiography and Surficial Geology 9
Extractive Activity 10
Selected Sand and Gravel Resource Areas 10
Selected Sand and Gravel Resource Area 1 10
Selected Sand and Gravel Resource Area 2 11
Selected Sand and Gravel Resource Area 3 11
Selected Sand and Gravel Resource Area 4 11
Sand and Gravel Resource Areas of Secondary Significance 11
Bedrock Geology 12
Selected Bedrock Resource Areas 12
Selected Bedrock Resource Area 1 12
Summary 13
References 22
Appendix A Suggested Additional Reading 23
Appendix B Glossary 24
Appendix C Geology of Sand and Gravel Deposits 27
Appendix D Geology of Bedrock Deposits 30

TABLES

1 - Total Sand and Gravel Resources, Smith Township 14
2 - Sand and Gravel Pits, Smith Township 15
3 - Selected Sand and Gravel Resource Areas, Smith Township 18
4 - Total Identified Bedrock Resources, Smith Township 19
5 - Quarries, Smith Township 20
6 - Selected Bedrock Resource Areas, Smith Township 21

FIGURES

1 - Key Map Showing Location of Smith Township v
2 - Bedrock Geology of Southern Ontario 30

MAPS
(back pocket)

1 - Distribution of Sand and Gravel Deposits, Smith Township, Scale 1:50 000.
2 - Selected Sand and Gravel Resource Areas, Smith Township, Scale 1:50 000.
3 - Bedrock Resources, Smith Township, Scale 1:50 000.

ABSTRACT



Figure 1. Key Map Showing Location of Smith Township. Scale 1:1 800 000.

An inventory and evaluation of aggregate resources, which include crushed stone derived from bedrock as well as natural sand and gravel, were completed for Smith Township in 1979. This report is part of the Aggregate Resources Inventory Program for townships and municipalities designated under The Pits and Quarries Control Act, 1971. The aggregate resources in the township have been assessed according to standards developed for the Program.

In Smith Township, four areas containing significant amounts of sand and gravel have been selected for possible resource protection. Selected Sand and Gravel Resource Areas consist of 1650 acres (670 ha), exclusive of licenced areas. An estimated 1400 acres (570 ha) are currently available for extraction, containing possible resources of 70 million tons (64 million tonnes). The parts of the Selected Areas which are available for extraction represent 29 percent of the total area occupied by sand and gravel deposits in the township and 32 percent of the total resource tonnage.

The first three Selected Sand and Gravel Resource Areas form part of a large esker deposit that occupies the central portion of the township. Resource Area 1 is the northern part of the deposit. It has an available area of 450 acres (182 ha), containing possible sand and gravel resources of 23 million tons (21 million tonnes). The aggregate is of good quality and is suitable for a wide range of road-building and construction uses.

Selected Sand and Gravel Resource Areas 2 and 3 are the more southerly portions of the esker deposit. They have a combined available area of 920 acres (373 ha) and possible resources estimated to be 46 million tons (41 million tonnes). The aggregate in these Areas is similar to that in Area 1.

Selected Sand and Gravel Resource Area 4 is a small kame deposit in the southern portion of the township. Approximately 1 million tons (1 million tonnes) of material are available.

Generally, Smith Township has possible sand and gravel resources which should be sufficient for local use for a considerable period of time. Care should be taken, nevertheless, to ensure the continuing availability of as much of the remaining resources as possible.

Large possible resources of crushed stone suitable for a wide range of aggregate products may be available in the northern portion of Smith Township. Bedrock Resource Area 1 consists of the entire extent of the Bobcaygeon Formation. It has an available area of 17,420 acres (7050 ha) with crushed stone resources of 3750 million tons (3400 million tonnes).

Selected Resource Areas are not intended to be permanent, single land use units which must be incorporated in an official planning document. They represent areas in which a major resource is known to exist. Such resource areas may be reserved wholly or partially for extractive development and/or resource protection within the context of the official plan.

AGGREGATE RESOURCES INVENTORY OF SMITH TOWNSHIP

BY
STAFF OF THE ENGINEERING
AND TERRAIN GEOLOGY SECTION

INTRODUCTION

Mineral aggregates, which include bedrock-derived crushed stone as well as naturally formed sand and gravel, constitute the major raw material in Ontario's road-building and construction industries. Very large amounts of these materials are used each year throughout the Province. For example, in 1976, the total tonnage of mineral aggregates extracted was greater than that of any other metallic or nonmetallic commodity mined in the Province (Ontario Ministry of Natural Resources 1977).

Although mineral aggregate deposits are plentiful in southern Ontario, they are fixed-location, nonrenewable resources which can be exploited only in those areas where they occur. Mineral aggregates are characterized by their high bulk and low unit value so that the economic value of a deposit is a function of its proximity to a market area as well as its quality and size. The potential for extractive development is usually greatest in urban fringe areas where land use competition is extreme. For these reasons the availability of adequate resources for future development is now being threatened in some areas.

Comprehensive planning and resource management strategies are required to make the best use of available resources, especially in those areas experiencing rapid development. Such strategies must be based on a sound knowledge of the total mineral aggregate resource base at both local and regional levels. The purpose of the Aggregate Resources Inventory is to provide the basic geological information required to include potential mineral aggregate resource areas in planning strategies and official plans. The reports should form the basis for discussion on those areas best suited for possible extraction. The aim is to assist decision-makers in protecting the public well-being by ensuring that adequate resources of mineral aggregate remain available for future use.

This report is a technical background document, based for the most part on geological information and interpretation. It has been designed as a component of the total planning process and should be used in conjunction with other planning considerations, to ensure the best use of a municipality's resources.

The report includes an assessment of sand, gravel and crushed bedrock. The most recent information available has been used to prepare the reports. As new information becomes available, revisions may be necessary.

PART I - INVENTORY METHODS

FIELD AND OFFICE METHODS

The methods used to prepare the report primarily involve the interpretation of published geological data such as bedrock and surficial geology maps and reports (see References). Wherever possible, field examination of potential resource areas was also undertaken to confirm interpretations made in the office. Field methods included the examination of natural and man-made exposures of granular material. Most observations were made at quarries and sand and gravel pits located from records held by the Ontario Ministry of Transportation and Communications, the Ontario Geological Survey, and by Regional and District Offices of the Ontario Ministry of Natural Resources. Observations made at pit sites included estimates of the total face height and the proportion of gravel- and sand-size fragments in the deposit. Observations were also made of the shape and lithology of the particles. These characteristics are important in estimating the quality and quantity of the aggregate. In areas of limited exposure, test pitting, soil probing and hand-augering techniques were used to assess subsurface materials. Air photos at various scales were used to determine the continuity of deposits, especially in areas of limited subsurface information.

In the office, the pit data were supplemented by information on file with the Engineering Materials Office of the Ontario Ministry of Transportation and Communications. Data contained in these files include field estimates of the depth, composition and "workability" of deposits as well as laboratory analyses of the physical properties and chemical suitability of the aggregate. Information concerning the development history of the pits and acceptable uses of the aggregate is also recorded. The location, size, and depth of extraction of pits licenced under The Pits and Quarries Control Act, 1971 were obtained from records held by Regional and District Offices of the Ontario Ministry of Natural Resources. The cooperation of the above named groups in the compilation of inventory data is gratefully acknowledged.

Water well records, held by the Ontario Ministry of the Environment, were used in some areas to corroborate thickness estimates, or to indicate the presence of buried granular material. These records were used only in conjunction with other evidence. Topographic maps of the National Topographic System, at a scale of 1:50 000, were used as a compilation base for the field and office data. The information was then transferred to a township base map, also at a scale of 1:50 000, prepared by the Cartography Section of the Lands and Waters Group, Ontario Ministry of Natural Resources, for presentation in the report.

RESOURCE TONNAGE CALCULATION TECHNIQUES

SAND AND GRAVEL RESOURCES

Once the interpretative boundaries of the aggregate units have been drawn, quantitative estimates of the possible resources available can be made. Generally, the volume of a deposit can be calculated if its areal extent and average thickness are known or can be estimated. The computation methods used are as follows: First, the area of the deposit, as outlined on the final base map, is calculated in acres. The thickness values used are an approximation of the deposit thickness, based on the face heights of pits developed in the deposit or on subsurface data such as water well logs. Original tonnage values can then be calculated by multiplying the volume of the deposit by 2500 (the density factor). This factor is approximately the number of tons in a one-foot thick layer of sand and gravel, one acre in extent, assuming an average density of 110 pounds per cubic foot.

Tonnage = Area x Thickness x Density Factor

Tonnage calculated in this manner must be considered only as an estimate. Furthermore, such tonnages represent amounts that existed prior to any extraction of material (i.e. original tonnage) (Table 1, Column 4).

The Selected Sand and Gravel Resource Areas in Table 3 represent only those parts of the deposit lying outside licenced areas (Column 2).

Two successive subtractions are made from the unlicenced area. Column 3 accounts for the number of acres unavailable due to the presence of permanent cultural features and their associated setback requirements. Column 4 accounts for those areas that have previously been extracted (e.g. wayside pits are included in this category). The remaining figure is the area of the deposit currently available for extraction (Column 5). The available area is then multiplied by the estimated deposit thickness and the density factor (Column 5 x Column 6 x 2500) to give an estimate of the sand and gravel tonnage presently available for extractive development and/or resource protection.

BEDROCK RESOURCES

The method used to calculate resources of bedrock-derived aggregate is much the same as that described above. The areal extent of favourrable bedrock formations overlain by less than 50 feet (15 m) of unconsolidated overburden is determined from bedrock geology maps, drift thickness and bedrock topography maps and from the interpretation of water well records. The measured extent of such areas is then multiplied by the estimated workable thickness of the formation, based on stratigraphic analyses and on estimates of existing quarry faces in the unit. In some cases a standardized estimate of a workable thickness of 60 feet (18 m) is used. Volume estimates are then multiplied by 3600 (the estimated weight in tons of a one-foot thick section of dolostone, one acre in extent, assuming a bulk density of 165 pounds per cubic foot).

Resources of sandstone are calculated using a bulk density estimate of 146 pounds per cubic foot or approximately 3200 tons per acre. Shale resources are calculated on the basis of a bulk density estimate of 150 pounds per cubic foot.

UNITS AND DEFINITIONS

Although most of the measurements and other primary data available for resource tonnage calculations are given in Imperial units, Metric units have also been given in the text and on the tables which accompany the report. The Metric equivalent of the data is shown in brackets after or directly below the corresponding Imperial figures. Data are generally rounded off in accordance with the Ontario Metric Practice Guide (Metric Committee 1975).

The tonnage estimates made for sand and gravel as well as bedrock-derived aggregates are termed possible resources in accordance with terminology of the Ontario Resource Classification Scheme (Robertson 1975,p.7) and with the Association of Professional Engineers of Ontario (1976) (see Glossary, Appendix B).

PART II - DATA PRESENTATION AND INTERPRETATION

Three maps, each portraying a different aspect of the aggregate resources in the municipality, accompany the report. Map 1, "Distribution of Sand and Gravel Deposits", gives a comprehensive inventory of the sand and gravel resources in the report area. Map 2, "Selected Sand and Gravel Resource Areas", shows those deposits which are considered to represent the largest and/or highest quality resources in the area. Map 3, "Bedrock Resources", shows the distribution of bedrock formations, the distribution of overlying unconsolidated sediments, and identifies the Selected Bedrock Resource Areas.

MAP 1: DISTRIBUTION OF SAND AND GRAVEL DEPOSITS

Map 1 is derived directly from the existing surficial geology maps of the area or from air photo interpretation where surficial mapping is incomplete. It shows the extent of sand and gravel deposits within the study area and serves as a base for the calculation of the total sand and gravel resources.

Map 1 presents a summary of all available information related to the quantity and quality of aggregate contained in all the known aggregate deposits in the study area. Much of this information is contained in the symbol which identifies each deposit. The Deposit Symbol is similar to those used in soil mapping and land classification systems commonly in use in North America. The components of the symbol indicate the gravel content, thickness of material, origin (type), and quality limitations for a given deposit. These components are illustrated by the following example:



This symbol identifies an outwash deposit 10 to 20 feet (3 to 6 m) thick containing more than 35 percent gravel. Excess fines may limit uses of the aggregate in the deposit.

The "gravel content" and "thickness class" are basic criteria for distinguishing different deposits. The "gravel content" symbol is an upper case "S" or "G". The "S" indicates that the deposit is generally "sandy" and that gravel-sized aggregate makes up less than 35 percent of the whole deposit. "G" indicates that the aggregate probably contains more than 35 percent gravel. If no information is available, the letters are omitted.

The "thickness class" indicates a depth range which is related to the potential resource tonnage for each deposit. Four thickness class divisions have been established as shown in the legend for Map 1.

Two smaller sets of letters, divided from each other by a horizontal line, follow the thickness class number. The upper series of letters identify the geologic deposit type (the types are summarized with respect to their main geologic and extractive characteristics in Appendix C) and the lower series of letters identify the main quality limitations that may be present in the deposit as discussed in the next section.

The other information presented on Map 1 is designed to give an indication of the present level of extractive activity in the study area. Those areas which are licenced for extraction under The Pits and Quarries Control Act, 1971 are shown by a solid outline and identified by a number which refers to the pit descriptions in Table 2. Each description notes the owner, location and licenced acreage of the pit, as well as the estimated face height and percentage gravel. A number of unlicenced pits are also identified and numbered on Map 1 and described in Table 2.

MAP 2: SELECTED SAND AND GRAVEL RESOURCE AREAS

Map 2 is an interpretative map derived from an evaluation of the deposits shown on Map 1. The deposits identified on Map 2 are those which are considered to be important in ensuring an adequate resource base for the future.

All the selected sand and gravel resource areas are first delineated by geological boundaries and then classified into three levels of significance: primary, secondary, and tertiary. These areas are identified on Map 2 by different shading patterns.

Each area of primary significance is assessed as to its probable relative value as a resource in the municipality and is given a deposit number which denotes its ranking order. All such deposits are shown by a medium-grey tone on Map 2.

Selected Aggregate Resource Areas of primary significance are not permanent, single land use units which must be incorporated in an official planning document. They represent areas in which a major resource is known to exist. Such resource areas may be reserved wholly or partially for extractive development and/or resource protection within the context of the official plan.

Deposits of secondary significance are not ranked numerically in this report, but are indicated by a light grey tone on Map 2. Such deposits are believed to contain significant amounts of sand and gravel. Although deposits of secondary significance are not considered to be the "best" resource areas in a municipality, they may contain large quantities of sand and gravel and should be considered an integral component of the aggregate supply of the municipality.

Areas of tertiary significance are indicated on the map by a dashed line but have no grey tone. They are neither rated nor considered to be important resource areas because of their low available resources, or because of possible difficulties in extraction. Such areas may be useful for local needs but are unlikely to support large-scale development.

The process by which deposits are evaluated and selected involves the consideration of two sets of criteria. The main selection criteria are site specific, related to the characteristics of individual deposits. Factors such as deposit size, aggregate quality, and deposit location and setting are considered in the selection of those deposits best suited for extractive development. A second set of criteria involves the assessment of local aggregate resources in relation to the quality, quantity, and distribution of resources in the region in which the municipality is located. The intent of such a process of evaluation is to ensure the continuing availability of sufficient resources to meet possible future demands.

SITE SPECIFIC CRITERIA

DEPOSIT SIZE

Ideally, selected deposits should contain available sand and gravel resources large enough to support a commercial pit operation using a stationary or portable processing plant. In practice, much smaller deposits may be of significant value depending on the overall reserves in the rest of the municipality. Generally, deposits in Class 1, i.e. those thicker than 20 feet (6m) and containing more than 35 percent crushable gravel are considered to be most favourable for commercial development. Thinner deposits may be valuable in municipalities with low total resources.

AGGREGATE QUALITY

The limitations of natural aggregates for various uses result from variations in the lithology of the particles composing the deposit, and from variations in the size distribution of these particles.

Four indicators of the quality of aggregate may be included in the symbol for each deposit on Map 1. They are: gravel content (G or S), fines (C), oversize (O) and lithology (L).

Three of the indicators deal with grain size distribution. The "gravel content", (G or S), indicates the suitability of aggregate for various uses. Deposits containing more than 35 percent crushable gravel are considered to be favourable extractive sites, since this content is the minimum from which crushed products can be economically produced.

Excess "fines" or high silt and clay content may severely limit the potential use of an aggregate. Fines content in excess of 10 percent may impede drainage in road sub-base aggregate and render it more susceptible to the effects of frost action. In asphalt aggregate, excess fines hinder the bonding of particles. Deposits known to have a high fines content are indicated by a "C" in the quality portion of the Deposit Symbol.

Deposits containing more than 20 percent "oversize" particles (those greater than 4 inches (10 cm) in diameter) may also have use limitations. The oversize component is unacceptable for all concrete aggregate and for road-building

aggregate, so must be either crushed or removed during processing. Deposits known to have an appreciable oversize component are indicated by an "O" in the quality portion of the Deposit Symbol.

The other indicator of the quality of an aggregate is "lithology". Just as the unique physical and chemical properties of bedrock formations determine their value for use as crushed rock, so do various lithologies of particles in a sand and gravel deposit determine its suitability for various uses. The presence of objectionable lithologies such as chert, siltstone, and shale, even in relatively small amounts, can result in a reduction in the quality of an aggregate, especially for high-quality uses. Deposits known to contain objectionable lithologies are indicated by an "L" in the quality component of the Deposit Symbol.

If the Deposit Symbol indicates either "C", "O" or "L" or any combination, the quality of the deposit is considered to be reduced for some uses of the aggregate. No attempt has been made to quantify the degree of limitation imposed. Assessment of the four indicators is made from published data, from data contained in files of the Ontario Ministry of Transportation and Communications and the Engineering and Terrain Geology Section of the Ontario Geological Survey, and from field observations. The Engineering Materials Office of the Ontario Ministry of Transportation and Communications has recently compiled a detailed assessment of aggregate suitability for selected areas in southern Ontario. This material has been consulted extensively in preparation of the inventory reports.

LOCATION AND SETTING

The location and setting of a resource area has a direct influence on its value for possible extraction. The evaluation of a deposit's setting is made on the basis of those natural and man-made features which may limit or prohibit extractive development.

First, the physical context of the deposit is considered. Deposits with some physical constraint on extractive development, such as thick overburden or high water table, are less valuable resource areas because of the difficulties involved in resource recovery. Second, permanent man-made features, such as roads, railways, powerlines, and housing developments, which are built on a deposit, may prohibit its extraction. The constraining effect of legally required setbacks surrounding such features is included in the evaluation. A quantitative assessment of these constraints can be made by measurement of their areal extent directly from the topographic maps. The area rendered unavailable by these features is shown for each resource area in Table 3.

The assessment of sand and gravel deposits and bedrock resource areas with respect to local land use and to private land ownership is an important component of the general evaluation process. These aspects of the evaluation process are not considered further in this report but readers are encouraged to discuss them with personnel of the Ontario Ministry of Natural Resources' District Office.

REGIONAL CONSIDERATIONS

In selecting sufficient areas for resource development, it is important to assess both the local and the regional resource base, and to forecast future production and demand patterns.

Some appreciation of future aggregate requirements in an area may be gained by assessing its present production levels and by forecasting future production trends. Such an approach is based on the assumptions that production levels in an area closely reflect the demand and that the present production "market share" of an area will remain at roughly the same level.

The aggregate resources in the region surrounding a municipality should be assessed in order to properly evaluate specific resource areas and to adopt optimum resource management plans. For example, a municipality that has large resources in comparison to its surrounding region constitutes a regionally significant resource area. Municipalities with high resources in proximity to large demand centres, such as metropolitan areas, are special cases.

Although an appreciation of the regional context is required to develop comprehensive resource management techniques, such detailed evaluation is beyond the scope of this report. The selection of resource areas made in this study is based primarily on geological data

or on considerations outlined in preceding sections.

MAP 3: BEDROCK RESOURCES

Map 3 is an interpretative map derived from bedrock geology, bedrock topography, drift thickness maps, water well data from the Ontario Ministry of the Environment, oil and gas well data from the Petroleum Resources Section (Ontario Ministry of Natural Resources), and from geotechnical well data from various sources. Map 3 is based on concepts similar to those outlined for Maps 1 and 2, but displays both the inventory and evaluation on the one map.

The geological boundaries of the labelled bedrock units are shown by a dashed line. Isolated outcrops are indicated by an "X". Three sets of contour lines delineate areas of less than 3 feet (1 m) of drift, areas of 3 to 25 feet (1 to 8 m) of drift, and areas of 25 to 50 feet (8 to 15 m) of drift. The extent of the areas of thin drift are shown by three tones. The darkest tone indicates areas where bedrock outcrops or is within 3 feet (1 m) of the ground surface. These areas constitute potential resource areas of primary significance due to their easy access. The medium tone indicates areas where drift cover is up to 25 feet (8 m) thick. Quarrying is possible in this depth of overburden and these also represent potential resource areas. The lightest tone indicates bedrock areas overlain by 25 to 50 feet (8 to 15 m) of overburden. These latter areas constitute resources which have extractive value only in specific circumstances. Outside of these delineated areas the bedrock can be assumed to be covered by more than 50 feet (15 m) of overburden, a depth generally considered to be too great to allow economic extraction (unless part of the overburden is composed of economically attractive sand and gravel deposits).

Other inventory information presented on Map 3 is designed to give an indication of the present level of extractive activity in the municipality. Those areas which are licenced for extraction under The Pits and Quarries Control Act, 1971 are shown by a solid outline and identified by a number which refers to the quarry descriptions in Table 5. Each description notes the owner, location, and licenced acreage of the quarry and an estimate of face height. Unlicenced quarries are also identified and numbered on Map 3 and described in Table 5. One additional symbol appears on the map: an open dot indicates the location of a selected well which penetrates bedrock. The overburden thickness is shown in feet beside the open dot.

SELECTION CRITERIA

Criteria equivalent to those used for sand and gravel deposits are used to select bedrock areas most favourable for extractive development.

The evaluation of bedrock resources is made primarily on the basis of performance and suitability data established by laboratory testing at the Ontario Ministry of Transportation and Communications. The main characteristics and uses of the bedrock formations found in southern Ontario are summarized in Appendix D.

Deposit "size" is related directly to the areal extent of thin drift cover overlying favourable bedrock formations of sufficient thickness to support quarry operations. Since vertical and lateral variations in bedrock units are much more gradual than in sand and gravel deposits, the quality and quantity of the resource is usually consistent over large areas.

Quality of the aggregate derived from specific bedrock units is established by the performance standards previously mentioned. Location and setting criteria and regional considerations are identical to those for sand and gravel deposits.

SELECTED RESOURCE AREAS

Selection of bedrock resource areas has been restricted to a single level of significance. Three factors support this approach. Quality and quantity variations are gradual. The areal extent of a given quarry operation is much smaller than that of a sand and gravel pit producing an equivalent tonnage of material. Since crushed bedrock has a higher unit value than sand and gravel, longer haul distances can be considered. These factors allow the identification of alternative sites having similar development potential. The wider range of possible resource areas allows greater flexibility in locating quarry operations away from areas of intensive land use competition. The Selected Areas are shown on Map 3 by a line pattern and the calculated available tonnages are given in Table 6.

Selected Bedrock Resource Areas shown on Map 3 are not permanent, single land use units which must be incorporated in an official planning document. They represent areas in which a major bedrock resource is known to exist. Such a resource area may be reserved wholly or partially for extractive development and/or resource protection within the context of the official plan.

PART III ASSESSMENT OF AGGREGATE RESOURCES IN SMITH TOWNSHIP

LOCATION AND POPULATION

Smith Township occupies an area of 59,347 acres (24 018 ha) in western Peterborough County. The township is bounded on the west, north and east by Chemung Lake, Buckhorn Lake and the Otonabee River, respectively; and by North Monaghan Township and the City of Peterborough on the south. The township is shown on portions of the Burleigh Falls (31D/9) and Peterborough (31D/8) map sheets of the National Topographic System at a scale of 1:50 000.

The hamlet of Bridgenorth, located on the western boundary of the township, is the only settlement entirely within the township. Portions of the Village of Lakefield and the City of Peterborough are located at the eastern and southern boundaries of the township. The population of the City of Peterborough was 59 305 in 1978 (Ontario Ministry of Intergovernmental Affairs 1979). Figures from previous years indicate that the city has experienced a relatively low rate of increase in the recent past (Ontario Ministry of Treasury, Economics and Intergovernmental Affairs 1974). Some residential development is occurring in the southern portion of Smith Township and it is probable that such development will continue in the future.

The total population of the township, including the unincorporated settlements, was 7602 in 1978 (Ontario Ministry of Intergovernmental Affairs 1979). Figures from the previous five years indicate that the population has increased by approximately 10 percent (Ontario Ministry of Treasury, Economics and Intergovernmental Affairs 1974). Many of the inhabitants are engaged in farming, although recently, the number of rural-residential and recreational inhabitants has increased. Similar growth patterns may be expected in the near future. Population projections for Peterborough County as a whole indicate that an increase of 15 to 20 percent may be expected by the year 2000 (Ontario Ministry of Treasury, Economics and Intergovernmental Affairs 1976). Consequently, the local demand for aggregates, both for road and building construction, will also probably increase.

Road access within the township is provided by gravel-surfaced township roads and by paved county roads. The area is also served by King's Highways 7, 28 and 507. Lines of the Canadian Pacific and the Canadian National Railways are located in the southern portion of the township.

PHYSIOGRAPHY AND SURFICIAL GEOLOGY

The physiography and distribution of unconsolidated sediments, including the sand and gravel deposits shown on Map 1, are the result of glacial activity which took place in the Late Wisconsinan Stage of the Pleistocene Epoch. This period of time, which lasted from approximately 23 000 to 12 500 years ago, was marked by the repeated advance and melting back of massive, continental ice sheets.

Smith Township was covered several times during the Late Wisconsinan by an ice mass that advanced to the southwest toward the Lake Ontario basin. The advancing ice deposited large amounts of till at its base, forming an extensive till plain throughout much of Peterborough County. The till was moulded in places into streamlined, elongated hills called drumlins. The till and associated drumlins form the Peterborough Drumlin Field (Chapman and Putnam 1966, p.280).

Smith Township is characterized, especially in the south, by many drumlin forms occurring singly or in groups and orientated in a southwest-northeast direction. Possible sand and gravel resources derived from drumlins are of minor importance in the township. The till which forms the drumlins and the till plain consists of unsorted sand, silt and stones. It is of little value as an aggregate source because of the excessive fines content. The till plain forms a thin veneer over bedrock throughout much of Smith Township, except in the extreme southern portions of the area.

The deglaciation of most of Peterborough County was accompanied by the melting-in-place (or "stagnation") of the ice mass. In many places, meltwaters flowing through tunnels or in crevasses in the ice deposited long trains of gravel and sand along their course. These deposits, known as eskers, form long, sinuous ridges which are up to 98 feet (30 m) in height and many miles (km) in length. The eskers have a similar orientation to that of the drumlins and are found throughout Peterborough County. The eskers, composed predominantly of gravel and sand, have been traditional sources of road and construction aggregate throughout the region. Nearly all of the gravel resources in Smith Township are found in a large esker and kame complex which trends to the northeast in the central portion of the township.

Postglacial erosional and depositional processes have been of relatively little importance in modifying the physiography of the township. Poor drainage in the thinly drift-covered northern and central portions of the township has resulted in the development of extensive marshy areas, such as the area near Snelgrove Brook.

EXTRACTIVE ACTIVITY

Extractive activity in Smith Township has been concentrated in the large esker-kame complex which trends to the northeast in the centre of the township. Approximately 80 percent of the pits opened in the township are developed in the esker deposit. Many pits have become inactive, since the designation of Smith Township under The Pits and Quarries Control Act, 1971. At the time of writing, a total of seventeen sources were licenced to operate. The total area licenced for extraction is 997.2 acres (403.6 ha). Using calculation techniques described in the Introduction, the remaining sand and gravel resources in the licenced properties are estimated to be 24.4 million tons (22.1 million tonnes).

Records of the total annual production of sand and gravel from all licenced sources have been maintained by the Lindsay District Office since designation of the township. The average annual production over the last three years has been approximately 0.4 million tons (0.4 million tonnes). Future production levels are expected to equal or exceed this figure.

SELECTED SAND AND GRAVEL RESOURCE AREAS

The sand and gravel deposits selected for possible resource protection in Smith Township are shown on Map 2. The entire extent of the Smith Township esker-kame deposit has been selected as a Sand and Gravel Resource Area of Primary Significance. Resource areas and tonnage for each numbered deposit are given in Table 3.

The Selected Sand and Gravel Resource Areas of Primary Significance have a total available area of 1400 acres (570 ha), containing resources of approximately 70 million tons (64 million tonnes). The Selected Resource Areas occupy 29 percent of the total area of sand and gravel deposits in Smith Township and represent 32 percent of the total resource tonnage. The Selected Areas contain virtually all of the township's resources of crushable aggregate.

SELECTED SAND AND GRAVEL RESOURCE AREA 1

Selected Sand and Gravel Resource Area 1 is the esker-kame deposit at the northern end of the esker, south of Youngs Point. The deposit consists of a main, indistinct ridge surrounded by smaller ridges and areas of irregular, hummocky topography.

Two licenced sources are developed in Area 1, as well as several inactive pits. Face heights in these pits range from 10 to 25 feet (3 to 8 m) and expose predominantly sandy material with coarse aggregate found in discontinuous pockets and lenses. There are several small esker ridges within the sandy material and these are preferred extractive sites. Aggregate from the pits has been used for a variety of road-building and construction products, including Granular Base Course A, B and C.

The deposit is often too sandy for crushing, although in some places excess oversize material poses crushing difficulties. In most cases the sand in the deposit contains appreciable amounts of fine-grained material, and is described as "dirty" and unsuitable for some types of hot-laid asphaltic aggregate. Blending of the sand will minimize this problem.

The Resource Area occupies 530 acres (214 ha), exclusive of licenced areas. Previous extraction and cultural constraints reduce the Resource Area to 450 acres (182 ha) presently

available for extraction. Assuming an average thickness of 20 feet (6 m), available sand and gravel resources are estimated to be 23 million tons (21 million tonnes).

SELECTED SAND AND GRAVEL RESOURCE AREA 2

Selected Sand and Gravel Resource Area 2 is the main ridge of the esker in the central portion of the township. The ridge varies in width and extends from the shore of Katchewanooka Lake in the east to Snelgrove Brook in the west. The ridge is made up of several large esker segments, as well as associated kame deposits and sandy, ice-contact stratified drift deposits on the esker and kame flanks.

Eight sources are presently licenced to operate in Area 2 and there are several presently inactive pits. The face heights in the pits range from 10 to 30 feet (3 to 9 m) and expose a range of material from massive, poorly stratified coarse gravels of the esker core, to well stratified layers of gravel and fine to coarse sand in the kames and in the sandy flanking deposits.

Aggregate suitability data obtained from the Ontario Ministry of Transportation and Communications indicate that the aggregate is acceptable for a wide range of road-building and construction products. In the areas of coarse gravel, processing may be required to remove large oversize cobbles and boulders in order to produce Granular Base Course A,B and C. In some areas, the sand fraction grades fine and "dirty" for hot-laid aggregate.

Much of Resource Area 2 is presently under licence and licenced resources are large. The portion of Area 2 lying outside of licenced areas occupies 930 acres (375 ha). It is estimated that only 130 acres (52 ha) of this total may be unavailable due to the presence of houses and roads or to previous extraction. Assuming an average deposit thickness of 20 feet (6 m), presently available sand and gravel resources are estimated to be 40 million tons (36 million tonnes). This is a resource of great importance in the region and can supply local needs for many years if properly protected. The land in Area 2 has limited potential for rural uses, and may be easily rehabilitated after extraction of the aggregate has been completed.

SELECTED SAND AND GRAVEL RESOURCE AREA 3

Selected Sand and Gravel Resource Area 3, extending from Snelgrove Brook to Bridgenorth, is the southernmost part of the esker in the township. The esker is well defined in this portion of the deposit and the flanking sandy deposits are much less well developed than those further north. The ridge is approximately 150 feet (46 m) wide and 35 feet (11 m) in height in Area 3.

Several pits have been developed in the deposit, two of which are presently licenced. Face heights in the pits are approximately 20 feet (6 m) and expose similar material to that found in Areas 1 and 2. The aggregate is also of similar quality to that in the other portions of the esker system and has been used for a wide range of products.

Area 3 consists of 155 acres (63 ha), exclusive of licenced areas. One hundred and twenty acres (49 ha) are estimated to be available for extraction. Assuming an average thickness of 20 feet (6 m), total available sand and gravel resources are estimated to be 6 million tons (5 million tonnes).

SELECTED SAND AND GRAVEL RESOURCE AREA 4

Selected Sand and Gravel Resource Area 4 is a small kame deposit which lies in the southernmost portion of the township. Most of the deposit is presently under licence with three pit operations. The aggregate in Area 4 consists of good-quality sand and minor gravel. The aggregate has been used for a range of products.

Area 4 consists of 35 acres (14 ha), exclusive of licenced areas. Constraints imposed by developments are minimal. Assuming an average deposit thickness of 20 feet (6 m), Selected Resource Area 4 has available resources of 1 million tons (1 million tonnes).

SAND AND GRAVEL RESOURCE AREAS OF SECONDARY SIGNIFICANCE

Additional granular material is available in a shallow outwash deposit that flanks the Smith Township esker, near Youngs Point. This deposit has been selected as a Sand and Gravel

Resource Area of Secondary Significance. Although the deposit is not the "best" resource area in the township, it should be considered an integral component of the aggregate supply.

BEDROCK GEOLOGY

Smith Township is underlain by a succession of bedrock formations ranging from Precambrian age granite and metamorphosed sediments in the northern portion of the township, to progressively younger limestones, dolostones and shales of the Shadow Lake, Gull River, Bobcaygeon, Verulam and Lindsay Formations, in the southern part of the township (Liberty 1969; Winder 1954).

Precambrian rocks are found under thin drift cover in the northern portion of the township near Mackenzie Bay. No detailed assessment of the Precambrian rock types has been made in this area. No areas have been selected for possible resource protection.

The Precambrian rocks are overlain by sandstones and siltstones of the Shadow Lake Formation. The formation is quite thin and is usually found only in depressions on the Precambrian bedrock surface. The Shadow Lake Formation has been combined with the Gull River Formation on Map 3 because of its extremely limited area of occurrence (Liberty 1969).

The Gull River Formation overlies the Shadow Lake Formation and occurs under thin drift cover in a relatively narrow band fringing Buckhorn Lake and Clear Lake. The Gull River Formation has been divided into four members, but generally may be described as a dense, fine-grained limestone with occasional dolostone layers (Liberty 1969). It is well suited for both road-building and construction aggregate, although a few of the beds are alkali-reactive and are not suitable for concrete aggregate (Dolar-Mantuani 1975). The Gull River Formation has been extracted at several quarries in the area, near Coboconk, Burnt River and Dongola. The total thickness of the three members is estimated to be 70 to 80 feet (21 to 24 m). It is considerably thinner near the contact with the underlying Precambrian rocks (Liberty 1969), and the formation is probably not thick enough for economic quarrying throughout its area of occurrence in Smith Township. The Gull River Formation has not been selected for possible resource protection.

The Gull River Formation is overlain by the Bobcaygeon Formation which is composed of thin-bedded, fine-grained limestone with some shaly partings. The Bobcaygeon Formation is also well suited for the production of road-building and construction aggregate and has been quarried elsewhere in the region near Kirkfield. The thickness of the formation ranges from 80 to 112 feet (24 to 34 m). The entire extent of the Bobcaygeon Formation covered by less than 25 feet (8 m) of drift has been selected for possible resource protection.

The Bobcaygeon Formation is overlain to the south by the Verulam Formation. The Verulam Formation underlies most of the township south of Youngs Point, except for a small area in the southernmost corner. The formation consists of fossiliferous, pure to impure limestone interbedded with thin layers of shale. It has been quarried elsewhere in the Province for use in the production of lime, but the stone is unsuitable for crushed products because of its low abrasion and freeze-thaw resistance. Consequently, no areas of the formation have been selected for resource protection. The Verulam Formation bedrock surface is relatively flat and drift thickness ranges from consistently less than 25 feet (8 m) in the north-central portion of the township to more than 50 feet (15 m) in the south-central portion. Quarries to produce lime might be established in numerous places in the north-central portion of the township, although extensive poorly drained areas would hinder extractive development.

The Verulam Formation is overlain in the extreme southern portion of the township by limestones and shales of the Lindsay Formation. Drift thickness over the Lindsay Formation is consistently greater than 100 feet (30 m) in this area and extractive development of the bedrock is not feasible by open pit method.

SELECTED BEDROCK RESOURCE AREAS

SELECTED BEDROCK RESOURCE AREA 1.

Selected Bedrock Resource Area 1 consists of the entire extent of the Bobcaygeon Formation overlain by less than 25 feet (8 m) of drift. Isolated bedrock exposures are common.

Area 1 occupies a total of 18,900 acres (7600 ha). Cultural constraints reduce the area available for extraction to 17,420 acres (7050 ha). There has been no previous extraction. Assuming an average quarriable thickness of 60 feet (18 m), possible crushed stone resources are estimated to be 3750 million tons (3400 million tonnes). . . . (3400 million tonnes). Parts of the Resource Area are poorly drained and may not be well suited for quarry development. Generally the Resource Area is sparsely populated and competing land uses are of minor importance. Quarries might be established at numerous places through out the Area.

SUMMARY

Smith Township has possible sand and gravel resources which should be available for local use for a considerable period of time. Four areas have been selected for possible resource protection. The Selected Resource Areas are portions of a large esker-kame deposit that dominates the physiography of Smith Township. Additional granular material is available in a Resource Area of Secondary Significance. Together, the Resource Areas contain most of the possible resources of crushable aggregate in the township.

Large possible resources of crushed stone are available in the northern portion of Smith Township. The entire extent of the thinly drift covered Bobcaygeon Formation in this area has been selected for possible resource protection.

Enquiries regarding the Aggregate Resources Inventory of Smith Township should be directed to the Ontario Ministry of Natural Resources either at the Lindsay District Office, 322 Kent St. W., Lindsay, Ontario, K9V 4T7, (Tel. (705) 324-6121) or at the Central Region Office, 10670 Yonge St., Richmond Hill, Ontario, L4C 3C9, (Tel. (416) 884-9203).

TABLE 1 | TOTAL SAND AND GRAVEL RESOURCES, SMITH TOWNSHIP

1 CLASS NO.	2 DEPOSIT TYPE (See Appendix C)	3 AREAL EXTENT (Acres) (Hectares)	4 ORIGINAL TONNAGE Millions of Tons (Tonnes)
1	G-E	670 (270)	34 (31)
	G-EK	1100 (445)	73 (66)
	G-IC	670 (270)	34 (31)
	S-K	40 (16)	2 (2)
	G-OW	40 (16)	2 (2)
	S-OW	110 (44)	7 (6)
2	S-E	25 (10)	1 (1)
	G-IC	200 (81)	8 (7)
	G-K	30 (12)	1 (1)
	S-K	235 (95)	9 (8)
	G-OW	720 (290)	32 (29)
3	S-K	110 (44)	2 (2)
	G-OW	360 (146)	7 (6)
4	S-LP	60 (24)	<1 (<1)
	G-OW	200 (81)	2 (2)
	S-OW	180 (73)	2 (2)
		4750 (1920)	216 (196)

N. B. Minor variations in above table are due to rounding of data.

TABLE 2 | SAND AND GRAVEL PITS, SMITH TOWNSHIP

1 NO.	2 MTC NO.	3 OWNER/OPERATOR	4 LOT	5 CON.	6 LICENCED AREAS Acres (Hectares)	7 FACE HEIGHT Feet (Metres)	8 % GRAVEL
LICENCED PITS							
1		K. Morris	30	11	200.0 (80.9)	15 (5)	60
2		I. Dunford	33	10	3.9 (1.6)	10 (3)	
3		Corp. of the County of Peterborough	28	10	6.0 (2.4)	25 (8)	70
4		Doughty Aggregates	26	9	54.0 (21.8)	20 (6)	-
5		Doughty Aggregates	23	8	97.0 (39.3)	20 (6)	30
6		R. Wilford	23	8	27.5 (11.1)	20 (6)	-
7		Pinewood Aggregates Ltd.	20-23	8	166.0 (67.2)	27 (8)	30
8		F. S. Coyle Ltd.	22	8	39.0 (15.8)	20 (6)	30
9		Doughty Aggregates	27, 28	6	44.3 (17.9)	10 (3)	-
10		Doughty Aggregates	17, 18	7	82.8 (33.5)	10 (3)	-
11		F. Nelson	13, 14 15	6	102.0 (41.3)	20 (6)	70
12		F. Nelson	11 ECR	6	26.0 (10.5)	20 (6)	-
13		J. D. O'Reilly	3, 4	5	8.0 (3.2)	25 (8)	65
14		F. Nelson & Sons Ltd.	7	3	9.0 (3.6)	18 (6)	10
15		H. V. Steinburg and Sons	6	3	32.5 (13.2)	15 (5)	10
16		Dunford Bros. Ltd.	6	3	47.2 (19.1)	38 (12)	10
17		Doughty Aggregates	24	8	52.0 (21.0)	10 (3)	
					997.2 (403.6)		

TABLE 2 | SAND AND GRAVEL PITS, SMITH TOWNSHIP

1 NO.	2 MTC NO.	3 OWNER/OPERATOR	4 LOT	5 CON.	6 LICENCED AREAS Acres (Hectares)	7 FACE HEIGHT Feet (Metres)	8 % GRAVEL
UNLICENCED PITS							
18	B3-39	R. Armstrong	27	18		10 (3)	-
19	B9-33	W. Northy	32	15		12 (4)	70
20	B9-13	A. Zinn	34	15		10 (3)	-
21	B9-6	I. Hordienko	33	14		10 (3)	-
22	P9-8	G. Green	32	14		10 (3)	-
23	P9-107	Dunford	30	12		15 (5)	-
24	P9-101	D. Lloyd	34	11		15 (5)	0-5
25	P9-20	Kidd #1	33	11		10 (3)	55
26	P9-97	I. Dunford	32	10		10 (3)	20
27	P9-127	Preston #3	28	10		10 (3)	45-65
28	P9-126	Preston #2	28	10		12 (4)	45-65
29	P9-141	Preston #4	28	10		15 (5)	45-65
30	P9-96	Preston #1	28	10		20 (6)	0-60
31	P9-125	A. Pitt	27	9		10 (3)	35-65
32	P9-51	Doughty	26	9		40 (12)	0-70

TABLE 2 | SAND AND GRAVEL PITS, SMITH TOWNSHIP

1 NO.	2 MTC NO.	3 OWNER/OPERATOR	4 LOT	5 CON.	6 LICENCED AREAS Acres (Hectares)	7 FACE HEIGHT Feet (Metres)	8 % GRAVEL
33	P9-129	Garvie #2	24	8		10 (3)	0-5
34	P9-132	Schrama	20	8		10 (3)	-
35	P9-81	Redpath	26	8		12 (4)	-
36	P9-18	Boyle	25	7		25 (8)	3
37	P9-131	Gill	18	7		25 (8)	40-70
38	P9-47	Unknown	26	5		10 (3)	-
39	P9-15	Hubbard	13	6		20 (6)	60
40	P9-37	Burton	10 ECR	6		20 (6)	65
41	P9-1	H. H. Dinsdale	11 WCR	6		20 (6)	0-5
42	P9-23	Hetherington	19	3		10 (3)	-
43	P9-11	Dunford Bros.	5	3		30 (9)	0-5

TABLE 3 | SELECTED SAND AND GRAVEL RESOURCE AREAS, SMITH TOWNSHIP

1 DEPOSIT NO.	2 UNLICENCED AREA Acres (Hectares)	3 CULTURAL SETBACKS Acres (Hectares)	4 EXTRACTED AREA Acres (Hectares)	5 AVAILABLE AREA Acres (Hectares)	6 ESTIMATED DEPOSIT THICKNESS Feet (Metres)	7 AVAILABLE AGGREGATE Millions of Tons (Tonnes)
1	530 (214)	70 (28)	10 (4)	450 (182)	20 (6)	23 (21)
2	930 (375)	90 (36)	40 (16)	800 (324)	20 (6)	40 (36)
3	155 (63)	20 (8)	15 (6)	120 (49)	20 (6)	6 (5)
4	35 (14)	5 (2)	0 (0)	30 (12)	20 (6)	1 (1)
	1650 (670)	185 (75)	65 (26)	1400 (570)		(70) (64)

N. B. Minor variations in above table are due to rounding of data.

TABLE 4 | TOTAL IDENTIFIED BEDROCK RESOURCES, SMITH TOWNSHIP

1 **DRIFT THICKNESS** Feet (Metres)	2 **FORMATION**	3 **WORKABLE THICKNESS** Feet (Metres)	4 **AREAL EXTENT** Acres (Hectares)	5 **ORIGINAL TONNAGE** Millions of Tons (Tonnes)
3-25 (1-8)	Gull River	10 (3)	2700 (1090)	97 (88)
25-50 (8-15)	Gull River	10 (3)	180 (73)	6 (5)
			2900 (1170)	103 (93)
3-25 (1-8)	Bobcaygeon	60 (18)	18,900 (7600)	4100 (3700)
25-50 (8-15)	Bobcaygeon	60 (18)	840 (340)	181 (164)
			19,700 (8000)	4300 (3900)
3-25 (1-8)	Verulum	60 (18)	13,400 (5400)	2890 (2600)
25-50 (8-15)	Verulam	60 (18)	3850 (1560)	830 (750)
			17,200 (7000)	3700 (3350)
			40,000 (16 200)	8100 (7300)

N. B. Minor variations in above table are due to rounding of data.

TABLE 5 QUARRIES, SMITH TOWNSHIP

1 NO.	2 MTC NO.	3 OWNER/OPERATOR	4 LOT	5 CON.	6 LICENCED AREA Acres (Hectares)	7 FACE HEIGHT Feet (Metres)
Q1		City of Peterborough	23	5		30 (9)

TABLE 6 | SELECTED BEDROCK RESOURCE AREAS, SMITH TOWNSHIP

1 DEPOSIT NO.	2 DEPTH OF OVERBURDEN Feet (Metres)	3 UNLICENCED AREA Acres (Hectares)	4 CULTURAL SETBACKS Acres (Hectares)	5 EXTRACTED AREA Acres (Hectares)	6 AVAILABLE AREA Acres (Hectares)	7 ESTIMATED WORKABLE THICKNESS Feet (Metres)	8 AVAILABLE TONNAGE Millions of Tons (Tonnes)
1	3-25 (1-8)	18,900 (7600)	1480 (600)	0 (0)	17,420 (7050)	60 (18)	3750 (3400)

N. B. Minor variations in above table are due to rounding of data.

REFERENCES

Association of Professional Engineers of Ontario
1976: Performance Standards for Professional Engineers Advising on and Reporting on Oil, Gas and Mineral Properties; 11p.

Carson, D. M.
1980: Paleozoic Geology of the Burleigh Falls - Peterborough Area, Southern Ontario; Ontario Geological Survey, Preliminary Map P.2337, scale 1:50 000.

Chapman, L. J. and Putnam, D. F.
1966: The Physiography of Southern Ontario; Second Edition, Ontario Research Foundation, University of Toronto Press, 386p.

Dolar-Mantuani, L.
1975: Petrography and Utilization of Paleozoic Middle Ordovician Carbonate Rocks in Southern Ontario; Ontario Division of Mines, Industrial Mineral Report 42, 59p.

Gravenor, C. P.
1957: Surficial Geology of the Lindsay-Peterborough Area, Ontario, Victoria, Peterborough, Durham and Northumberland Counties, Ontario; Geological Survey of Canada, Memoir 288, 60p., 1 map, scale 1:250 000.

Liberty, B. A.
1969: Paleozoic Geology of the Lake Simcoe Area, Ontario; Geological Survey of Canada, Memoir 355, 201p., 1 map, scale 1:253 440.

Ontario
1979: The Pits and Quarries Control Act, 1971; Statutes of Ontario, 1971, Chapter 96, Queen's Printer for Ontario.

Ontario Interministerial Committee on National Standards and Specifications (Metric Committee)
1975: Metric Practice Guide; 67p.

Ontario Ministry of Intergovernmental Affairs
1979: Municipal Directory 1979; Queen's Printer for Ontario, 190p.

Ontario Ministry of Natural Resources
1977: Ontario Mineral Review 1976-77; Ontario Ministry of Natural Resources, 95p.

Ontario Ministry of Treasury, Economics and Intergovernmental Affairs
1974: Municipal Directory 1974; Queen's Printer for Ontario, 128p.

1976: Ontario's Changing Population, Volume II Directions and Impact of Future Change 1971-2001; Regional Planning Branch, 184p.

Robertson, J. A.
1975: Mineral Deposit Studies, Mineral Potential Evaluation and Regional Planning in Ontario; Ontario Division of Mines, Miscellaneous Paper 61, 42p.

Winder, C. G.
1954: Burleigh Falls and Peterborough Map Areas, Ontario; Geological Survey of Canada, Paper 53-27, 10p., 2 maps, scale 1:63 360.

APPENDIX A-SUGGESTED ADDITIONAL READING

American Geological Institute
1972: Glossary of Geology; Washington, D.C., 858 p.

Bauer, A. M.
1970: A Guide to Site Development and Rehabilitation of Pits and Quarries; Ontario Department of Mines and Northern Affairs, Industrial Mineral Report 33, 62p.

Cowan, W. R.
1977: Towards the Inventory of Ontario's Mineral Aggregates; Ontario Geological Survey, Miscellaneous Paper 73, 19p.

Fairbridge, R.W. (ed.)
1968: The Encyclopedia of Geomorphology; Encyclopedia of Earth Sciences, Vol. III, Reinhold Book Corp., N.Y., 1295p.

Flint, R.F.
1971: Glacial and Quaternary Geology; John Wiley and Sons Inc., 892p.

Guillet, G.R.
1967: The Clay Products Industry of Ontario; Ontario Department of Mines, Industrial Mineral Report 22, 206p.

Hewitt, D.F.
1960: The Limestone Industries of Ontario; Ontario Department of Mines, Industrial Mineral Report 5, 177p.
1964a: Building Stones of Ontario, Part I Introduction; Ontario Department of Mines, Industrial Mineral Report 14, 43p
1964b: Building Stones of Ontario, Part II Limestone; Ontario Department of Mines, Industrial Mineral Report 15. 41p
1964c: Building Stones of Ontario, Part III Marble; Ontario Department of Mines, Industrial Mineral Report 16, 89p.
1964d: Building Stones of Ontario, Part IV Sandstone; Ontario Department of Mines, Industrial Mineral Report 17, 57p
1972: Paleozoic Geology of Southern Ontario; Ontario Division of Mines, Geological Report 105, 18p.

Hewitt, D. F. and Karrow, P. F.
1963: Sand and Gravel in Southern Ontario; Ontario Department of Mines, Industrial Mineral Report 11, 151p.

Hewitt, D. F. and Vos, M. A.
1970: Urbanization and Rehabilitation of Pits and Quarries; Ontario Department of Mines, Industrial Mineral Report 34, 21p.

Ontario Mineral Aggregate Working Party
1977: A Policy for Mineral Aggregate Resource Management in Ontario; Ontario Ministry of Natural Resources, 232p.

Ontario Ministry of Natural Resources
1975: Vegetation for the Rehabilitation of Pits and Quarries; Forest Management Branch, Division of Forests, 38p.

Proctor and Redfern Ltd.
1974: Mineral Aggregate Study, Central Ontario Planning Region; Prepared for the Ontario Ministry of Natural Resources, over 100p., some coloured maps.

Proctor and Redfern Ltd., and Gartner Lee Associates Ltd.
1975: Mineral Aggregate Study of Part of The Eastern Ontario Region; Prepared for the Ontario Ministry of Natural Resources, about 200p.

1977: Mineral Aggregate Study and Geological Inventory, Southwestern Region of Ontario; Prepared for the Ontario Ministry of Natural Resources, about 200 p., some coloured maps.

APPENDIX B-GLOSSARY

ABRASION RESISTANCE

Tests such as the Los Angeles Abrasion Test are used to measure the ability of aggregate to resist crushing and pulverizing under conditions similar to those encountered in processing and use. Measuring resistance is an important component in the evaluation of the quality and prospective uses of aggregate. Hard, durable material is preferred for road building.

ABSORPTION CAPACITY

Related to the porosity of the rock types of which an aggregate is composed. Porous rocks are subject to disintegration when absorbed liquids freeze and thaw, thus decreasing the strength of the aggregate.

AGGREGATE

Any hard, inert, construction material (sand, gravel, shells, slag, crushed stone or other mineral material) used for mixing in various sized fragments with a cement or bituminous material to form concrete, mortar, etc., or used alone for road building or other construction. Synonyms include mineral aggregate and granular material.

CAMBRIAN

The first Period of the Paleozoic Era, thought to have covered the time between 570 and 500 million years ago; the Cambrian precedes the Ordovician Period.

CLAST

An individual constituent, grain, or fragment of a sediment or rock, produced by the mechanical weathering of a larger rock mass. Synonyms include particle and fragment.

DELETERIOUS LITHOLOGY

A general term used to designate those rock types which are chemically or physically unsuited for use as construction or road-building aggregates. Such lithologies as chert, shale, siltstone, and sandstone may deteriorate rapidly when exposed to traffic and other environmental conditions.

DEVONIAN

A Period of the geological past thought to have covered the span of time between 395 and 345 million years ago, following the Silurian Period. Rocks formed in the Devonian Period are among the youngest found in Ontario.

DIRT

See fines.

DOLOSTONE

A carbonate sedimentary rock consisting chiefly of the mineral dolomite and containing relatively little calcite (dolostone is also known as dolomite).

DRIFT

A general term for all unconsolidated rock debris transported from one place and deposited in another; distinguished from underlying bedrock. In North America, glacial activity has been the dominant mode of transport and deposition of drift. Synonyms include overburden and surficial deposit.

DRUMLIN

A low, smoothly rounded, elongated hill, mound, or ridge composed of glacial materials. These landforms were deposited beneath an advancing ice sheet, and were shaped by its flow.

EOLIAN

Pertaining to the wind, especially with respect to landforms whose constituents were transported and deposited by wind activity. Sand dunes are an example of an eolian landform.

FINES

A general term used to describe the size fraction of an aggregate which passes (is finer than) the No.200 mesh screen (0.074 mm). Also described informally as "dirt", these particles are in the silt- and clay-size range.

GLACIAL LOBE

A tongue-like projection from the margin of the main mass of an ice cap or ice sheet. During the Pleistocene Epoch several lobes of the Laurentide continental ice sheet occupied the Great Lakes basins. These lobes advanced and retreated numerous times during the Pleistocene, producing the complex arrangement of glacial material and landforms found in southern Ontario.

GRADATION

The proportion of material of each particle size, or the frequency distribution of the various sizes which constitute a sediment. The strength, durability, permeability and stability of an aggregate depend to a great extent on its gradation. The size limits for different particles are as follows:

Boulder		>-256 mm
Gravel	cobble	64-256 mm
Gravel	pebble	4-64 mm
Gravel	granule	2-4 mm
Sand	coarse	.5-2 mm
	medium	.25-.5 mm
	fine	.074-.25 mm
Silt, clay		<.074 mm

GRANULAR BASE COURSE

Components of the pavement structure of a road, which are placed on the subgrade and are designed to provide strength, stability, and drainage, as well as support for surfacing materials. Several types have been defined: Granular Base Course A consists of crushed and processed aggregate and has relatively stringent quality standards in comparison to Granular Base Course B and C which are usually pit-run or other unprocessed aggregate.

H.L. (HOT-LAID OR ASPHALTIC AGGREGATE)

Bituminous, cemented aggregates used in the construction of pavements either as surface or bearing course (H.L. 1, 3, and 4), or as binder course (H.L. 2, 6, and 8) used to bind the surface course to the underlying granular base course.

LITHOLOGY

The description of rocks on the basis of such characteristics as color, structure, mineralogic composition, and grain size. Generally, the description of the physical character of a rock.

MELTWATER CHANNEL

A drainage way, usually terraced, produced by water flowing away from a melting glacier margin.

ORDOVICIAN

An early period of the Paleozoic Era thought to have covered the span of time between 500 and 435 million years ago.

PALEOZOIC ERA

One of the major divisions of the geologic time scale thought to have covered the time between 570 and 230 million years ago. The Paleozoic Era (or Ancient Life Era) is subdivided into six geologic Periods, of which only four (Cambrian, Ordovician, Silurian, and Devonian) can be recognized in southern Ontario.

PLEISTOCENE

An Epoch of the recent geological past including the time from approximately 1.8 million years ago to 7000 years ago. Much of the Pleistocene was characterized by extensive glacial activity.

POSSIBLE RESOURCE

Reserves estimates based largely on broad knowledge of the geologic character of the deposit and for which there are few, if any samples or measurements. The estimates are based on assumed continuity or repetition for which there are reasonable geological indications.

SHALE

A fine-grained, sedimentary rock formed by the consolidation of clay, silt, or mud and characterized by well developed bedding planes, along which the rock breaks readily into thin layers. The term shale is also commonly used for fissile claystone, siltstone, and mudstone.

SILURAIN

An early Period of the Paleozoic Era thought to have covered the time between 435 and 395 million years ago. The Silurian follows the Ordovician Period and precedes the Devonian Period.

SOUNDNESS

The ability of the components of an aggregate to withstand the effects of various weathering processes and agents. Unsound lithologies are subject to disintegration caused by the expansion of absorbed solutions. This may seriously impair the performance of road-building and construction aggregates.

TILL

Unsorted and unstratified rock debris, deposited directly by glaciers, and ranging in size from clay to large boulders.

WISCONSINAN

Pertaining to the last glacial stage of the Pleistocene Epoch in North America. It began approximately 85,000 years ago and ended approximately 7000 years ago. The glacial deposits and landforms of southern Ontario are predominantly the result of glacial activity during the Wisconsinan Stage.

APPENDIX C-GEOLOGY OF SAND AND GRAVEL DEPOSITS

The type, distribution, and extent of sand and gravel deposits in southern Ontario are the result of extensive glacial and glacially influenced activity in Wisconsinan time during the Pleistocene Epoch, approximately 7000 to 85 000 years ago. The deposit types reflect the different depositional environments that existed during the melting and retreat of the continental ice masses, and they can readily be differentiated on the basis of their morphology, structure, and texture. The deposit types are described below.

GLACIOFLUVIAL DEPOSITS

These deposits can be divided into two broad categories: those that were formed in contact with (or in close proximity to) glacial ice, and those that were deposited by meltwaters carrying materials beyond the ice margin.

ICE-CONTACT TERRACES (ICT)

These are glaciofluvial features deposited between the glacial margin and a confining topographic high, such as the side of a valley, The structure of the deposits may be similar to that of outwash deposits, but in most cases the sorting and grading of the material is more variable and the bedding is discontinuous due to extensive slumping. The probability of locating large amounts of crushable aggregate is moderate, and extraction may be expensive due to the variability of the deposits both in terms of quality and grain-size distribution.

KAMES (K)

Kames are defined as mounds of poorly sorted sand and gravel deposited by meltwater in depressions or fissures on the ice surface or at its margin. During glacial retreat, the melting of supporting ice causes collapse of the deposits producing internal structures characterized by bedding discontinuities. The deposits consist mainly of irregularly bedded and cross-bedded, poorly sorted sand and gravel. The present forms of the deposits include single mounds, linear ridges (crevasse fillings) or complex groups of landforms. The latter are occasionally described as "undifferentiated ice-contact stratified drift" (IC) when detailed subsurface information is unavailable. Since kames commonly contain large amounts of fine-grained material and are characterized by considerable variability, there is generally a low to moderate probability of discovering large amounts of good-quality, crushable aggregate. Extractive problems encountered in these deposits are mainly the excessive variability of the aggregate and the rare presence of excess fines (silt-and clay-sized particles).

ESKERS (E)

Eskers are narrow, sinuous ridges of sand and gravel deposited by meltwaters flowing in tunnels within or at the base of glaciers, or in channels on the ice surface. They vary greatly in size. Many, though not all eskers consist of a central core of poorly sorted and stratified gravel characterized by a wide range in grain size. The core material is often draped on its flanks by better sorted and stratified sand and gravel. The deposits have a high probability of containing a large proportion of crushable aggregate, and since they are generally built above the surrounding ground surface, are convenient extraction sites. For these reasons esker deposits have been traditional aggregate sources throughout southern Ontario, and are significant components of the total resources of many areas.

Some planning constraints and opportunities are inherent in the nature of the deposits. Because of their linear nature, the deposits commonly extend across several property boundaries leading to unorganized extractive development at numerous small pits. On the other hand, because of their form, eskers can be easily and inexpensively extracted and are amenable to rehabilitation and sequential land use.

UNDIFFERENTIATED ICE-CONTACT STRATIFIED DRIFT (IC)

This designation may include deposits from several ice-contact, depositional environments which usually form extensive, complex landforms. It is not feasible to identify individual areas of coarse-grained material within such deposits due to their lack of continuity and grain-size variability. They are given a qualitative

rating based on existing pit and other subsurface data.

OUTWASH (OW)

Outwash deposits consist of sand and gravel laid down by meltwaters beyond the margin of the ice lobes. They occur as sheets or as terraced valley fills (valley trains) and may be very large in extent and thickness. Well developed outwash deposits have good horizontal bedding and are uniform in grain-size distribution. Outwash deposited near the glacier's margin is much more variable in texture and structure. The probability of locating useful crushable aggregates in outwash deposits is moderate to high depending on how much information on size, distribution and thickness is available.

ALLUVIUM (AL)

Alluvium is a general term for clay, silt, sand, gravel, or similar unconsolidated material deposited during postglacial time by a stream as sorted or semi-sorted sediment, on its bed or on its floodplain. The probability of locating large amounts of crushable aggregate in alluvial deposits is low, and it has generally low value due to the presence of excess silt- and clay-sized material. There are no large postglacial alluvium deposits in Ontario.

GLACIOLACUSTRINE DEPOSITS

GLACIOLACUSTRINE BEACH DEPOSITS (LB)

These are relatively narrow, linear features formed by wave action at the shores of glacial lakes that existed at various times during the deglaciation of southern Ontario. Well developed lacustrine beaches are usually less than 20 feet (6 m) thick. The aggregate is well sorted and stratified and sand-sized material commonly predominates. The composition and size distribution of the deposit depends on the nature of the underlying material. The probability of obtaining crushable aggregate is high when the material is developed from coarse-grained materials such as a stony till, and low when developed from fine-grained materials. Beaches are relatively narrow, linear deposits, so that extractive operations are often numerous and extensive.

GLACIOLACUSTRINE DELTAS (LD)

These features were formed where streams or rivers of glacial meltwater flowed into lakes and deposited their suspended sediment. In southern Ontario such deposits tend to consist mainly of sand and abundant silt. However, in near-ice and ice-contact positions, coarse material may be present. Although deltaic deposits may be large, the probability of obtaining coarse material is generally low.

GLACIOLACUSTRINE PLAIN (LP)

The nearly level surface marking the floor of an extinct glacial lake. The sediments which form the plain are predominantly fine to medium sand, silt, and clay, and were deposited in relatively deep water. Lacustrine deposits are generally of low value as aggregate sources due to their fine grain size and lack of crushable material. In some aggregate-poor areas, lacustrine deposits may constitute valuable sources of fill and some granular base course aggregate.

GLACIAL DEPOSITS

END MORAINES (EM)

These are belts of glacial drift deposited at, and parallel to, glacier margins. They commonly consist of ice-contact stratified drift and in such instances are usually called kame moraines. Kame moraines commonly result from deposition between two glacial lobes (interlobate moraines). The probability of locating aggregates within such features is moderate to low. Exploration and development costs are high. Moraines may be very large and contain vast aggregate resources, but the location of the best resource areas within the moraine is usually poorly defined.

EOLIAN DEPOSITS

WINDBLOWN FORMS (WD)

Windblown deposits are those formed by the transport and deposition of sand by winds. The form of the deposits ranges from extensive, thin layers to well developed linear and crescentic ridges known as dunes. Most windblown deposits in southern Ontario are derived from,

and deposited on , pre-existing lacustrine sand plain deposits. Windblown sediments are almost invariably composed of fine to coarse sand and are usually well sorted. The probability of locating crushable aggregate in windblown deposits is very low.



Figure 2 - Bedrock Geology of Southern Ontario

BEDROCK SUITABLE FOR CRUSHED STONE PRODUCTS

BASS ISLANDS FORMATION (UPPER SILURIAN)

(Includes the Bertie Formation of the Niagara Peninsula) Composition: Medium- to massive-bedded, aphanitic, brown dolostone with shaly partings. Thickness: 35 to 60 feet (11-18m) near Hagersville. Uses: Quarried for crushed stone on the Niagara Peninsula at Fort Erie, Cayuga, Hagersville, and Dunville. Los Angeles Abrasion Test: 17-35% loss; Absorption: 1.4%. Shaly parts are unsuitable for aggregate due to high soundness losses.

BOBCAYGEON FORMATION (MIDDLE ORDOVICIAN)

Composition: Compact, homogeneous, medium- to thin-bedded, fine-grained limestone with some argillaceous and shaly partings. Thickness: The lower unit is 40 to 72 feet (12 to 22 m) thick in the east and the remainder of the formation is 40 feet (12 m). Uses: Quarried at Kirkfield and Marysville for crushed stone. The Bobcaygeon Formation has consistently acceptable quality for granular base course materials and concrete.

BOIS BLANC FORMATION (LOWER-MIDDLE DEVONIAN)

Composition: Brownish grey, medium-crystalline, medium- to thin-bedded, cherty limestone, commonly fossiliferous. Limestone may be silty or sandy in places. Thickness: 9 to 200 feet (3 to 61 m). Uses: Quarried at Hagersville, Cayuga, and Port Colborne for crushed stone. High chert content makes much of the material unsuitable for concrete aggregate. Los Angeles Abrasion

Test: 14-28% loss; Soundness Test: 4-10% loss; Absorption: 0.7-2.0%.

DUNDEE FORMATION (MIDDLE DEVONIAN)

Composition: Fine- to medium-crystalline, brown ish grey, medium- to thick-bedded, dolomitic limestone with shaly partings, sandy layers, and chert in some areas. Thickness: 60 to 160 feet (18 to 49 m). Uses: Quarried near Port Dover and Pelee Island for crushed stone. Used at St. Marys for portland cement. Los Angeles Abrasion Test: 22-32% loss; Absorption: 0-4%.

GULL RIVER FORMATION (MIDDLE ORDOVICIAN)

Composition: Member A: thin-to thick-bedded, interbedded, grey argillaceous limestone and buff to green dolostone with a maximum thickness of 60 feet (18 m). Members B and C are dense, aphanitic limestones with argillaceous dolostone interbeds. Uses: Quarried at Kirkfield, Victoria County, and Uthoff for crushed stone. The product is generally fresh and compact with good cubic-shaped factor, low clay content, low absorption, and low soundness losses. Smooth particle surfaces may cause adhesion problems for asphalt. There is some alkali reactivity in a few of the layers.

LOCKPORT AND AMABEL FORMATIONS (MIDDLE SILURIAN)

Composition: Amabel Formation (Georgetown to the Bruce Peninsula): massive, fine crystalline dolostone, with reef facies dolostone near Georgetown. Lockport Formation (lateral facies equivalent to the Amabel Formation from Georgetown to Niagara Falls): thin- to massive-bedded, fine- to medium-grained dolostone. Thickness: Amabel Formation: maximum observed thickness of 84 feet (26 m). Lockport Formation: up to 130 feet (40 m). Uses: The Lockport and Amabel Formations have been used to produce lime, crushed stone, and building stone throughout their area of occurrence, and are a valuable aggregate resource. Los Angeles Abrasion Test: 21-35% loss; Soundness Test: 2.0% loss; Absorption: 0.4-1.6%.

ONONDAGA FORMATION (MIDDLE DEVONIAN)

(Equivalent to the Detroit River Group, with a textural change) Composition: Edgecliffe Member: medium-bedded, fine- to medium-grained, dark grey cherty limestone with an estimated thickness of 25 to 30 feet (8 to 9 m). Clarence Member: massive-bedded, dark grey brown, fine-grained, very cherty limestone having an estimated thickness of 26 feet (8 m). Moorehouse Member: medium-bedded, dark grey brown or purplish brown, fine- to coarse-grained, variably cherty limestone with an estimated thickness of 15 to 25 feet (5 to 8 m). Uses: Quarried for crushed stone on the Niagara Peninsula at Welland and Port Colborne. High chert content makes much of the material unsuitable for concrete aggregate.

OTTAWA FORMATION (MIDDLE ORDOVICIAN)

Composition: Lower Phase (Lowville and Pamela Beds): shale, some sandstone and dolostone. Thickness: 100 feet (30 m). Middle Phase (Hull, Rockland, and Leray Beds): pure, thick-bedded, crystalline limestone. Thickness: 150 feet (46 m) near Ottawa. Upper Phase (Cobourg and Sherman Fall Beds): pure and impure crystalline limestone with few to numerous shaly partings, 450 to 475 feet (137–145 m) thick near Ottawa. Uses: The Leray, Rockland, and Hull Beds have been quarried extensively for crushed stone and for building stone. In addition, the Hull Beds are an excellent source of lime for cement production and agricultural uses.

OXFORD FORMATION (LOWER ORDOVICIAN)

Composition: Medium- to thick-bedded, grey dolostone, with some shaly partings. Thickness: 240 feet (73 m). Uses: Quarried for crushed stone (road and concrete aggregate) at Ottawa, Brockville, and Smiths Falls.

BEDROCK SUITABLE FOR LIME PRODUCTION AND OTHER CHEMICAL USES.

DETROIT RIVER GROUP (MIDDLE DEVONIAN)

(Equivalent to the Onondaga Formation in the Niagara Peninsula, with a textural change). Composition: Near Beachville, the group consists of medium- to micro-crystalline, medium-bedded, high purity limestone. It grades northwards near St. Marys to soft, evenly bedded, fine-grained dolostone with bituminous laminae. Massive, porous, reef facies material also occurs to the north (Formosa Reef Limestone). Thickness: 100 feet (30 m) at Beachville, 350 feet (107 m) at Clinton. Uses: The most important

source of high purity limestone in Ontario is the Lucas Formation of the Detroit River Group at Beachville. Detroit River limestone produces 80% of Ontario's cement. Its dolomitic reefal facies is also important for lime production to the north. It is generally unsuitable for crushed stone. The Anderdon Member of the Lucas Formation is quarried at Amherstburg for crushed stone.

GRENVILLE MARBLE (PRECAMBRIAN)

Composition: Recrystallized white limestone and dolostone, fine- to coarse-grained, usually of high chemical purity. Uses: Lime production, but also in small amounts for terrazo chips, poultry grit, decorative stone, and building stone.

GUELPH FORMATION (MIDDLE SILURIAN)

Composition: Aphanitic- to medium-crystalline, thick-bedded, soft, porous dolostone, characterized in places by extensive vuggy, porous reefal facies dolostone of high chemical purity. The Guelph Formation and the underlying Amabel Formation have a combined thickness of 200 feet (61 m) on the Niagara Peninsula and more than 400 feet (122 m) on the Bruce Peninsula. Uses: The main use is for dolomitic lime in the construction industry. It is quarried at Glen Christie and Guelph.

LINDSAY FORMATION (MIDDLE ORDOVICIAN)

Composition: Lower Member: fine-crystalline, rubbly, nodular, weathering limestone. Upper Member: grey calcareous claystone with shaly partings and bioclastic layers. The rock is "soft" and weathers to rubble. Both members are characterized by low dolomite content and by numerous clayey partings. Uses: Quarried at Picton, Ogden Point, Colborne, and Bowmanville for lime. It is generally unsuitable for crushed stone, concrete aggregate, or granular base course.

VERULAM FORMATION (MIDDLE ORDOVICIAN)

Composition: Fossiliferous, pure to argillaceous limestone and interbedded calcareous shale. The rock is not resistant to erosion and commonly weathers to rubble. Thickness: 200-300 feet (61-91 m). Uses: Quarried at Picton, Ogden Point, and Mara Township for lime. It is unsuitable for crushed stone due to clay impurities and many clayey interbeds, low abrasion resistance, high soundness losses and poor freeze-thaw resistance.

BEDROCK SUITABLE FOR BRICK AND TILE MANUFACTURE

GEORGIAN BAY FORMATION (UPPER ORDOVICIAN)

(Formerly known as the Meaford-Dundas and Blue Mountain shales in the Toronto and Bruce Peninsula areas). Composition: Soft, fissile, blue grey shale with limey or sandy lenses in a few places. Thickness: 640 feet (195 m) at Toronto. Uses: Five producers in Metro Toronto and Cooksville produce brick and structural tile (Guillet 1967). Lightweight aggregate is also produced at Streetsville by heat expansion of the shale.

HAMILTON GROUP (MIDDLE DEVONIAN)

Composition: Grey shale with interbeds of crystalline and cherty limestone. The Group has six formations. Only the Arkona is of commercial value. It is a soft, light grey, calcareous shale which is plastic and easily worked when wet. Thickness: 80 to 300 feet (24 to 91 m). Uses: The Arkona Formation is extracted at Thedford and near Arkona for production of drainage tile and brick.

QUEENSTON FORMATION (UPPER ORDOVICIAN)

Composition: Red, thin- to thick-bedded, sandy to argillaceous shale with green mottling and banding. Thickness: 400 to 500 feet (122 to 152 m). Uses: There are 12 large shale quarries developed in the Queenston Formation in the Toronto-Hamilton region and one at Russell, near Ottawa (Guillet 1967). All produce brick for construction. The Queenston Formation is the most important source material for brick manufacture in the Province.

BEDROCK SUITABLE FOR OTHER INDUSTRIAL PRODUCTS

NEPEAN (POTSDAM) FORMATION (CAMBRO-ORDOVICIAN)

Composition: Creamy, coarse-grained, silica sandstone. Uses: Quarried throughout its area of outcrop for building stone, decorative stone, abrasives, and for glass making.

SALINA FORMATION (UPPER SILURIAN)

Composition: Grey and red shale, brown dolomite, and, in places, salt, anhydrite, and gypsum. The formation consists predominantly of evaporite deposits with up to eight members identified. Uses: Gypsum is mined at Hagersville, Caledonia, and Drumbo. Salt is mined at Goderich and is produced from brine wells at Amhertsburg, Windsor, and Sarnia.

WHITBY FORMATION (UPPER ORDOVICIAN)

(Formerly known as Collingwood Shale near Toronto). Composition: Brown to black fissile shale. Uses: Quarried at Bowmanville for use in cement production. Testing indicates that the Whitby Formation may produce satisfactory lightweight expanded aggretage.

DEER BAY
LOWER BUCKHORN LAKE
REACH
Three Islands
Wolf Island
Lovesick Lake
Burleigh Falls
Bridgenorth
Locks
Taylors
Marshall
Grassy Island
Craft Point
Freeman Pt
Monroe Point
Johnsons Point
Red Buck I
Long Pines Pt
Traynor Pt
Sisters Is
Black Point
Dinnertime
Gray Duck Dam
Trent Canal
Hall Pt
Nicholls Pt
Wood Wharf Pt
BUCKHORN
Brown Pt
Wharves
LAKE
HARVEY TP
SMITH TP
McIlmoy Pt
Scotsman Point
Tanner Pt
DEER BAY
Pearsons Point
Wharf
Moore Lake
Young's Point
Marina
South Beach
Polly
Radio
TRENT CANAL
KAWARTHA LAKES
Douglas I
Katchewanooka Lake
Third Island
Second Island
Selwyn
Curve Lake
Coppaway Pt
Hermaden Narrows
Upper Chemung Lake
Chemung Narrows
Big Island
Bissett I
Birch I
MUD LAKE
IR 35
Snake I
Lute Pt
Seaweed Islands
Camray
XVIII
XVII
XVI
XV
XIV
XIII
XII
XI
796
793
800
808
912
845
861
876
807
879
18
19
20
21
22
23
24
25
27
28
29
30
0 49T
0 15SG
0 16G
0 20G
2 5G
1 36SG 9S
0 37G
0 25T
0 78GST
2T 29S
0 25T
6T
12T
14S 10G
25T 12G
1 49G
0 40G
1 40SG
1 7G
G 2 IC
G 1 E-K
G 1 E-K
G 2 OW
G 2 OW
S 2 E
S 2 E
507
28

Ministry of Natural Resources

Hon. James A.C. Auld
Minister

Dr. J.K. Reynolds
Deputy Minister

Ontario

ONTARIO GEOLOGICAL SURVEY

AGGREGATE RESOURCES INVENTORY

SMITH TOWNSHIP

PETERBOROUGH COUNTY

MAP 1
DISTRIBUTION OF SAND AND GRAVEL DEPOSITS

Scale: 1:50,000

Mile 1 0 1 Mile

Metres 1000 0 1 Kilometre

NTS Reference: 31D/8, 31D/9

© OMNR-OGS 1980



SYMBOLS

(Some symbols may not apply to this map)

- Geological and aggregate thickness boundary. Shading indicates deposit area.
- S1 IC CLO — Deposit symbol: see below.
- 3 — Licenced property boundary; Property number: see Table 2.
- 4 — Unlicenced sand or gravel pit; Property number: See Table 2.
- 6/23 — Selected drilling location indicating thickness of overburden overlying reported thickness of granular materials (in feet) (Note: S-sand, G-gravel, C-clay, T-till)

LAKEFIELD
Curve Lake
Selwyn
Bridgenorth
Chemung Park
Trent University
Trailer Park
Auto Wreckers
Skeet Club
Abandoned Airfield
Transformer Station
Pump House
Theatre
Race Grounds
Marina
Douglas I
Webster I
Second Island
Third Island
Birch I
Coppaway Pt
Lute Pt
Hall Pt
Causeway
Swing
Ditch
Abandoned
Dump
GP
Upper Chemung Lake
Katchewanooka Lake
Herriman Narrows
Fifth Ave
Tindle Bay
Horseshoe
Douro Tp
Smith Tp
Ennismore Tp
Smith Tp
Trent Canal
Canadian National Railways
S 2 E
G 2 OW
G 1 E
G 1 IC
G 2 OW
G 1 E
G 1 OW
S 4 OW
G 2 K
S 2 E
S 1 K
G 1 E
S 1 OW
G 2 IC
G 1 E
G 1 E-K
G 3 OW
G 1 E
S 1 K
G 1 E
S 1 OW
S 3 K
XII
XI
X
IX
VIII
VII
VI
V
IV
III
II
I

SYMBOLS

(Some symbols may not apply to this map)

- Geological and aggregate thickness boundary. Shading indicates deposit area.
- S 1 IC CLO — Deposit symbol: see below.
- 3 — Licenced property boundary; Property number: see Table 2.
- 4 — Unlicenced sand or gravel pit; Property number: See Table 2.
- 6/23 — Selected drilling location indicating thickness of overburden overlying reported thickness of granular materials (in feet) (Note: S-sand, G-gravel, C-clay, T-till).

DEPOSIT SYMBOL

Deposits are identified by gravel content, thickness class, deposit type and quality indicators. Gravel content is expressed as percentage of crushable material. Classes are based on potential aggregate tonnage per acre and are designated numerically. Type refers to geologic origin. Quality modifiers indicate variations in grain size distribution and lithology.

Gravel Content	Thickness Class	Geological Type
		Quality Indicators

Gravel Content

G	Greater than 35% gravel.
S	Less than 35% gravel.
?	Requires investigation.

Thickness Class

Class	Average Thickness in feet (metres)	Tons per acre (Tonnes per hectare)
1	greater than 20 (> 6)	greater than 50,000 (> 18 500)
2	10-20 (3-6)	25,000-50,000 (9 000-18 500)
3	5-10 (1.5-3)	12,500-25,000 (4 500-9 000)
4	less than 5 (< 1.5)	less than 12,500 (< 4 500)

Geological Type

IC	Undifferentiated Ice-Contact Stratified Drift	OW	Outwash
		LB	Lacustrine Beach
ICT	Ice-Contact Terrace	LP	Lacustrine Plain
K	Kame	LD	Lacustrine Delta
E	Esker	AL	Older Alluvium
EM	End Moraine	WD	Windblown Forms

(see Appendix C for descriptions of Geological Types.)

Quality Indicators

	If blank, no known limitations present
C	Clay and/or silt (fines) present in objectionable quantities
L	Deleterious lithologies present
O	Oversize particles or fragments present in objectionable quantities

PETERBOROUGH

SMITH TP

NORTH MONAGHAN TP

Chemung Park

Horseshoe I.

Marina

Campsite

Race Track

Transformer Station

Abandoned Airfield

Brick Works

Golf Course

Concrete Plant

Trent University

Pump House

Skeet Club

Theatre

Lily L.

Tanks

Park

Ditch

GP

CANADIAN NATIONAL RAILWAYS

C N

CHEMUNG RIVER

Trndle R.

G 1 E

S 1 OW

S 3 K

S 2 K

G 4 OW

S 4 LP

N

SMITH

	(1.5-3)	(4 500-9 000)
4	less than 5 (< 1.5)	less than 12,500 (< 4 500)

Geological Type

IC	Undifferentiated Ice-Contact Stratified Drift	OW	Outwash
		LB	Lacustrine Beach
ICT	Ice-Contact Terrace	LP	Lacustrine Plain
K	Kame	LD	Lacustrine Delta
E	Esker	AL	Older Alluvium
EM	End Moraine	WD	Windblown Forms

(see Appendix C for descriptions of Geological Types.)

Quality Indicators

	If blank, no known limitations present
C	Clay and/or silt (fines) present in objectionable quantities
L	Deleterious lithologies present
O	Oversize particles or fragments present in objectionable quantities

SOURCES OF INFORMATION

Base map by Surveys and Mapping Branch, Ontario Ministry of Natural Resources.
Licence data from District and Regional Offices, Ontario Ministry of Natural Resources.
Aggregate suitability data from the Engineering Materials Office Ontario Ministry of Transportation and Communications.
Selected drilling data from the Ontario Ministry of the Environment and the Petroleum Resources Section, Ontario Ministry of Natural Resources.

Geology by D.M. Carson, 1980
C.P. Gravenor, 1957

Compilation and Drafting by: Staff of the Aggregate Assessment Office.

Issued 1980

This map is published with the permission of E.G. Pye, Director, Ontario Geological Survey.

This map is to accompany O.G.S. Aggregate Resources Inventory Paper 15.

DEER BAY
LOWER BUCKHORN LAKE
REACH
Traynor Pt
Long Pines Pt
Three Sisters Is
Red Buck I
Johnsons Point
Craft Point
Three Islands
Grassy Island
Wolf Island
Lovesick Lake
Burleigh Falls
Taylors Pt
793
Marshall I
Dam
Lovesick Lock
Millage I
796
Gray Duck Dam
Monroe Point
Black Point
Dinnertime
XVIII
XVII
XVI
XV
XIV
XIII
XII
XI
18
19
20
21
22
Hall Pt
808
Nicholls Pt
Wood Wharf Pt
Trent Canal
BUCKHORN
Brown Pt
Wharves
912
Tanner Pt
DEER BAY
Wharf
Pearsons Point
845
861
876
507
28
LAKE
HARVEY TP
SMITH TP
McIlmoy Pt
Scotsman Point
Cavendish
Sewed Islands
MUD LAKE
IR 35
Snake I
Lute Pt
Big Island
Blewett I
Chemung Narrows
Upper Chemung Lake
Birch I
Coppaway Pt
Curve Lake
Harrington Narrows
Selwyn
879
Moore Lake
Young's Point
Radio
Marina
GP
Polly
South Beach
TRENT CANAL
KAWARTHA LAKES
Douglas I
Kaichewaung Lake
Third Island
1
23
24
25
27
28
30

Ministry of Natural Resources

Ontario

Hon. James A.C. Auld
Minister

Dr. J.K. Reynolds
Deputy Minister

ONTARIO GEOLOGICAL SURVEY
AGGREGATE RESOURCES INVENTORY

SMITH TOWNSHIP
PETERBOROUGH COUNTY

MAP 2
SELECTED SAND AND GRAVEL RESOURCE AREAS

Scale: 1:50,000

Mile 1 0 1 Mile

Metres 1000 0 1 Kilometre

NTS Reference: **31D/8, 31D/9**

© OMNR-OGS 1980



SYMBOLS
(Some symbols may not apply to this map)

- Geological and aggregate thickness boundary.
- Selected sand and gravel resource area; Primary significance; Deposit number: see Table 3.
- Selected sand and gravel resource area; Secondary significance.
- Selected sand and gravel resource area; Tertiary significance.
- 2 — Licenced property boundary; Property number: see Table 2.
- 4 — Unlicenced sand or gravel pit; Property number: See Table 2.

Seaweed Islands
Big Island
Chemung Narrows
Lake
Moore Lake
Young's Point
LAKES
TRENT CANAL
Radio
Marina
South Beach
Polly
Blewett I
MUD LAKE
IR 35
Snake I
Lute Pt
Birch I
Upper Chemung
Douglas I
Coppaway Pt
Curve Lake
Selwyn
Herrington Narrows
Katchewanooka Lake
Third Island
Second Island
Webster
DOURO TP
SMITH TP
Hall Pt
LAKEFIELD
Chimney 195'
Racetrack
Golf Greens
ENNISMORE TP
SMITH TP
LAKE
CHEMUNG
Causeway
Swing
Transformer Station
Bridgenorth
Chemung Park
Trailer Park
Dump
TRENT CANAL
NATIONAL
RIVER
XIV
XIII
XII
XI
X
IX
VIII
VI
V
879
819
885
1
2
3
4
5
6
7
8
9
10
11
17
23
24
25
27
28
30
32
34
35
36
37
39
40

SYMBOLS

(Some symbols may not apply to this map)

- Geological and aggregate thickness boundary.
- Selected sand and gravel resource area; Primary significance; Deposit number: see Table 3.
- Selected sand and gravel resource area: Secondary significance.
- Selected sand and gravel resource area; Tertiary significance.
- 2 — Licenced property boundary; Property number: see Table 2.
- 4 — Unlicenced sand or gravel pit; Property number: See Table 2.

SOURCES OF INFORMATION

Base map by Surveys and Mapping Branch, Ontario Ministry of Natural Resources.
Licence data from District and Regional Offices, Ontario Ministry of Natural Resources.
Aggregate suitability data from the Engineering Materials Office, Ontario Ministry of Transportation and Communications.
Selected drilling data from the Ontario Ministry of the Environment and the Petroleum Resources Section, Ontario Ministry of Natural Resources.

Geology by: D.M. Carson, 1980
C.P. Gravenor, 1957

Compilation and Drafting by: Staff of the Aggregate Assessment Office.

Issued 1980

This map is published with the permission of E.G. Pye, Director, Ontario Geological Survey.

This map is to accompany O.G.S. Aggregate Resources Inventory Paper 15.

CHEMUNG

Causeway
Swing
Marina
Transformer Station
Bridgenorth
Chemung Park
Marina
Park
Ditch
Abandoned
Skeet Club
Silo
Horseshoe
Fife Bay
Marina
Race Track
Campsite
Abandoned Airfield
Brick Works
Tanks
Trailer Park
Theatre
Pump House
Trent University
GARVADAN
NATIONAL
RIVER
Golf Course
TV 800
Microwave 200
Concrete Plant
City Limits
PETERBOROUGH
Radio 250
Poles
Park
Lily L
Transformer Station
C N
SMITH TP
NORTH MONAGHAN TP
GP
Ditch
I
II
III
IV
V
VI
2
3
4
11
12
13
14
15
16
38
39
40
41
42
43
805
885
N

Theatre
Trailer Park
38
R I V E R
CANADIAN NATIONAL
Theatre
Ditch
Pump House
Ditch
Trent University
GP
GP
GP
Concrete Plant
Golf Course
TV 600'
Microwave 200'
Ditch
N

SMITH


PRECAMBRIAN
BUCKHORN
LAKE
DEER
BAY
LOWER
REACH
BUCKHORN
LAKE
PRECAMBRIAN
GULL RIVER FORMATION
BOBCAYGEON FORMATION
PRECAMBRIAN
LAKE
GULL RIVER FORMATION
BOBCAYGEON FORMATION
BOBCAYGEON FORMATION
VERULAM FORMATION
BOBCAYGEON FORMATION
Trent Canal
Hall Pt
Nicholls Pt
Brown Pt
Wharves
Johnsons Point
Long Pine Pt
Three Sisters Is
Craft Point
Traynor Pt
Three Islands
Grassy Island
Wolf Island
Lovesick Lake
Burleigh Falls
Taylors I
Marshall I
Tanner Pt
Wharf
Pearsons Point
DEER BAY
Wharves
HARVEY TP
SMITH TP
McIlmoyl Pt
Scotsman Point
Big Island
Chemung Narrows
Upper Chemung Lake
Sawed Islands
Snake I
Lute Pt
Birch I
Coppaway Pt
Curve Lake
Hiawatha Narrows
Peterborough
Marina
South Beach
TRENT CANAL
KAWARTHA LAKES
Douglas I
Katchewanooka Lake
Third Island
Second Island
Webster

Ontario Ministry of Natural Resources

Minister

Dr. J.K. Reynolds
Deputy Minister

Ontario

ONTARIO GEOLOGICAL SURVEY
AGGREGATE RESOURCES INVENTORY

SMITH TOWNSHIP

PETERBOROUGH COUNTY

MAP 3
BEDROCK RESOURCES

Scale: 1:50,000

Mile 1 0 1 Mile

Metres 1000 0 1 Kilometre

NTS Reference: **31D/8, 31D/9**

© OMNR-OGS 1980



LEGEND

PALEOZOIC

ORDOVICIAN

MIDDLE ORDOVICIAN

LINDSAY FORMATION
Limestone

VERULAM FORMATION
Limestone

BOBCAYGEON FORMATION
Limestone

GULL RIVER FORMATION
Limestone

PRECAMBRIAN

Precambrian rocks

SYMBOLS

(Some symbols may not apply to this map.)

Geological boundary.

25 Drift thickness contour line (25 foot (8 m) interval).

LAKE CHEMUNG

ENNISMORE TP
SMITH TP

DOURO TP
SMITH TP

VERULAM FORMATION

LAKEFIELD

PETERBOROUGH

Bridgenorth

Chemung Park

Horseshoe

Fife Bay

Marina

Causeway Swing

Transformer Station

Gravel Pit

Abandoned Airfield

Brick Works

Tanks

Race Track

Composite

Skeet Club

Golf Course

Concrete Plant

Pump House

Trent University

Third Island

Second Island

Webster

Dump

Ditch

Park

City Limits

CANADIAN NATIONAL R.

TRENT CANAL

I

II

III

IV

V

VI

VII

VIII

IX



Limestone

PRECAMBRIAN

Precambrian rocks

SYMBOLS

(Some symbols may not apply to this map.)

- Geological boundary.
- 25 — Drift thickness contour line (25 foot (8 m) interval).
- x — Isolated bedrock outcrop.
- Bedrock within 3 feet (1 m) of surface: see Table 4.
- Bedrock covered by 3 to 25 feet (1 m to 8 m) of overburden: see Table 4.
- Bedrock covered by 25 to 50 feet (8 m to 15 m) of overburden: see Table 4.
- 1 — Selected bedrock resource area; Deposit number: see Table 6.
- Q3 — Licenced quarry boundary; Property number: See Table 5.
- Q4 — Unlicenced quarry; Property number; See Table 5.
- O 27 — Selected drilling location indicating reported depth to bedrock (in feet).

SOURCES OF INFORMATION

Base map by Surveys and Mapping Branch, Ontario Ministry of Natural Resources.
Licence data from District and Regional Offices, Ontario Ministry of Natural Resources.
Aggregate suitability data from the Engineering Materials Office, Ontario Ministry of Transportation and Communications.
Selected drilling data from the Ontario Ministry of the Environment and the Petroleum Resources Section, Ontario Ministry of Natural Resources.

Geology by: D.M. Carson, 1980
C.P. Gravenor, 1957

Compilation and Drafting by: Staff of the Aggregate Assessment Office.

Issued 1980

This map is published with the permission of E.G. Pye, Director, Ontario Geological Survey.

This map is to accompany O.G.S. Aggregate Resources Inventory Paper 15.


PETERBOROUGH
LINDSAY FORMATION
SMITH TP
NORTH MONAGHAN TP
Marina
Fire Boy
Abandoned Airfield
Brick Works
Tanks
City Limits
Race Track
Campsite
Transformer Station
Transformer Station
Radio 250
Golf Courses
Concrete Plant
Concrete Plant
Park
Ditch
GP
C N
C P
N

GP
GP
Golf
Course
TV
800'
Microwave
200'
Concrete
Plant
Concrete
Plants

SMITH